

## Aral Aktiengesellschaft

# Aral SuperTronic G SAE 0W-30

### Applications:

Aral SuperTronic G SAE 0W-30 is a fully synthetic high performance engineoil especially developed for Mercedes-Benz and Opel gasoline and diesel engines with long drain intervals.

The high performance of this product provides longest drain intervals with less fuel and oil consumption.

Aral SuperTronic G SAE 0W-30 outperforms demanding requirements of Mercedes-Benz, BMW and General Motors for engines with low emission for less fuel and oil consumption.

### Specification:

ACEA A3/B3, A3/B4

API SL / CF

### Approval:

MB-Approval 229.3/ 229.5

GM-LL-A-025, GM-LL-B-025

VW 502 00/ 505 00

BMW Longlife-01

meets FIAT 9.55535-G1

### Technical Data

SAE-grade		DIN 51511	0W-30
Density at 15 °C	g/ml	DIN 51757	0,840
Viscosity			
100 °C	mm <sup>2</sup> /s	DIN 51562	12,2
40 °C	mm <sup>2</sup> /s	DIN 51562	72
Viscosity -35 °C	cP	DIN 51377	5800
Viscosity Index		DIN ISO 2909	167
Flash point COC	°C	DIN ISO 2592	212
Pourpoint	°C	DIN ISO 3016	< -54

### Remarks:

<br>

All data is subject to development for the product and the production process.

Version-No.: AS3004100015