


AXLE GEOMETRY					C5										
Front axle					→ RPO 9435										
All types (except CARLSSON)					Rear axle										
Vehicle	Tracking	Castor	Camber	King pin inclination	Tracking	Camber									
	Adjustable	Non adjustable			Non adjustable										
All types	0 à - 3 mm 0° à - 0° 27'	3° 03' ± 30'	0° ± 30'	12° 56' ± 30'	5,4 ± 1,3 mm 0° 49' ± 0° 12'	- 1° ± 20'									
					RPO 9436 →										
					Rear axle										
					Tracking		Camber		Non adjustable						
					4,5 ± 1,3 mm 0° 41' ± 0° 12'		- 1° ± 20'								
<p><b>NOTE:</b> Front of the vehicle indicated by the arrow</p>					<table border="1"> <thead> <tr> <th colspan="3">NOTE</th> </tr> </thead> <tbody> <tr> <td>A &lt; B = Positive figure:</td> <td>+ =</td> <td>TOE-IN</td> </tr> <tr> <td>A &gt; B = Negative figure:</td> <td>- =</td> <td>TOE-OUT</td> </tr> </tbody> </table>		NOTE			A < B = Positive figure:	+ =	TOE-IN	A > B = Negative figure:	- =	TOE-OUT
NOTE															
A < B = Positive figure:	+ =	TOE-IN													
A > B = Negative figure:	- =	TOE-OUT													

B3CP02UC